



PM-WCS-3-I2C I2C Capacitive soil moisture, temperature sensor

FEATURES

- Arduino and Raspberry Pi client software libraries.
- Dust and waterproof
- Calibration functions for Dielectric permittivity (and Expermatal EC)
- Low cost and easy to use.
- Fairly accurate readings





PM-WCS-3-I2C I2C Capacitive soil moisture, temperature sensor

ELECTRICAL PROPERTIES

	Min/Sleep	Typical	Max
Supply voltage (VCC), V	2.2	3.3	5v
Working current (VCC=3.6V), mA	-	12	14
Operating Temperature Range, Celsius	-20	25	70

In case your application needs to power up sensor before measurement, time to wait before taking measurement is 100ms (1.7s for old version before v1.1).

MEASUREMENT PROPERTIES

	Resolution	Range /avg Tolerance
Dielectric permittivity (ϵ) (Temperature corrected)	0.1 ϵ	1 (air) to 80 (water) /5%
Expermetal EC, Electrical Conductivity (mS/m) (0.1 mS/m = 1 uS/cm)	0.1 mS/m	0...300 mS/m 20% 300...800 mS/m 40%
Temperature (°C)	0.1°C	-20 to 70°C/3%
Degree of water saturation in the soil Volumetric water content - VWC calculation from Dielectric permittivity ϵ . $VWC = 0.002974 * \text{pow}(\epsilon, 2) + 0.07424 * \epsilon - 1.295$;	0.1%	0 - 100% /8%

PHYSICAL PROPERTIES

Sensor dimensions 114 x 24 x11
Cable length 1.4m 2,9m; 4,9m



PM-WCS-3-I2C I2C Capacitive soil moisture, temperature sensor

RASPBERRY PI

wiring to Raspberry Pi connector:

Raspberry Pi pin #1 - sensor **red** (3.3v)
Raspberry Pi pin #3 - sensor **green** (SDA)
Raspberry Pi pin #5 - sensor **white** (SCL)
Raspberry Pi pin #9 - sensor **black** (GND)
Raspberry Pi pin #9 - sensor shield(GND)

Enable i2c interface in Raspberry Pi

see [this manual](#)

Get software

This sample software demonstrates how to make command line interface for the sensor. Sensor default I2C address is 0x63.

To get software execute following on Raspberry Pi:

```
git clone https://github.com/tinovi/i2cRaspberry
```

```
cd i2cRaspberry
```

```
chmod 777 *.sh to add permissions for execute
```

```
./mk.sh to make demo executable
```

```
./read.sh to read data from sensor
```

```
./svcs 0x63 addr 0x65 ( optional) to change default address 0x63 to new I2C address: 0x65
```

CALIBRATION RASPBERRY

- 1) Download and install raspberry pi software described in previous section
- 2) **cd i2cRaspberry** - cd to software directory
- 3) **./read.sh** - read data
- 4) **./cal_air.sh** - hold sensor in the air, and execute this command to calibrate sensor in the air
- 5) **./cal_water.sh** - submerge sensor in the water or soil with the water, and execute this command to calibrate water.
- 6) **./cal_ec.sh <ec uS/m>** - put sensor to the soil or calibration fluid with known uS/m and write correct uS/m
- 7) **./read.sh** - read data



PM-WCS-3-I2C I2C Capacitive soil moisture, temperature sensor

ARDUINO

SDA and SCL lines require pullup resistors ~4.7k

wiring to Arduiono:

Arduiono pin #3V3 - sensor **red** (3.3v)

Arduiono pin #A4 - sensor **green** (SDA)

Arduiono pin #A5 - sensor **white** (SCL)

Arduiono pin #GND - sensor **black** (GND)

Arduiono pin #GND - sensor shield (GND)

Get software

This sample software demonstrates how to read data from sensor.

Sensor default I2C address is 0x63.

Download Arduino library from [there](#).